



RG214 COAXIAL CABLE



Product Description
COAX RF RG214 PVC

Technical Specifications
Reference: 30-120-8

Product Overview

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	Coaxial cables used for Radio-Frequency designed according to the International Standard IEC 1196

Physical Characteristics (Overall)

Conductor

Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
Stranded	SPCCS - Silver Plated Copper Covered Steel	7x0.75 mm	2.25 mm	0.03 mm	1

Conductor Count:	1
Conductor Size:	13 AWG

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	Polyethylene	7.25 mm	0.2 mm

Outer Shield Material

Type	Layer	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	1	SPC - Silver Plated Copper	86 %	8 mm	0.25 mm	4 %
Braid	2	SPC - Silver Plated Copper	90 %	8.7 mm	0.25 mm	4 %

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	10.8 mm	0.2 mm

OuterJacket1, Table Note: According to European Standard HD 624

Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
6 Ohm/km	9.1 Ohm/1000ft	3.1 Ohm/km

Capacitance

Norm. Capacitance	Capacitance Tolerance
100 pF/m	3 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
50 Ohm	± 0.5 %



50 Ohm	2 Ohm
--------	-------

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
50 MHz	4.3 dB/100m
230 MHz	9.9 dB/100m
470 MHz	14.9 dB/100m
860 MHz	21.3 dB/100m
1000 MHz	23.3 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
66 %	2 %

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
100 - 1000 MHz	23 dB

Power Rating

Frequency [MHz]	Nominal Power Rating [W]
100 MHz	760 W
1,000 MHz	175 W

Voltage

Voltage Test Dielectric
3.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	110 mm
Crush Resistance:	Max. 1% (load of 700N) N

Standards

ISO/IEC Compliance:	IEC 1196
CPR Euroclass:	Eca
RG Type:	214/U Type

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
---------------------------------------	------------

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

